

VANDAL PROOF DOME CAMERA

TDC-2104ASD5, TDC-2104AFD5

540TVL / CMOS MINI VANDAL PROOF DOME CAMERA



TDC-2104ASD5
Surface Mount Type



TDC-2104AFD5
Flush Mount Type

- FEATURES -

- 1/3" CMOS Image Sensor
- 540TV Lines Horizontal Resolution
- Excellent Low Light Sensitivity of 0.1Lux/F1.2
- Auto White Balance
- Auto Gain Control
- Board Lens f=3.6mm
- IP66 Weatherproof Type
- Vandal Proof Dome Housing
- Compact Design



1/3 CMOS
IMAGE SENSOR



3.6mm
BOARD LENS



IP 66





VANDAL PROOF





DC 12V

- DIMENSION -

Surface Mount Type



Flush Mount Type



- SPECIFICATIONS -

TDC-2104ASD5 / TDC-2104AFD5	
Signal Format	NTSC / PAL
Horizontal Resolution	540TV Lines
Image Sensor	1/3" CMOS Image Sensor
Total Pixels	762(H) x 504(V)
Effective Pixels	728(H) x 488(V)
Scanning System	2:1 Interlace
Synchronization	Internal
Scanning Frequency	15.734 KHz(H), 59.94 Hz(V)
Video Output	CVBS : 1.0Vp-p/75Ω
Min. Illumination	0.1Lux/F1.2
Iris Control	Auto
Signal to Noise Ratio	More than 48dB
White Balance	Auto
Gain Control	Auto
Lens	Board Lens f=3.6mm
Input Voltage	DC 12V (±10%)
Power Consumption	Max. 0.8W
Operating Temperature	-10°C ~ +50°C
Operating Humidity	30% ~ 90% RH
Dimension	TDC-2104ASD5 : 80.0(Ø) x 60.5(H)mm TDC-2104AFD5 : 88.0(Ø) x 58.5(H)mm
Weight	TDC-2104ASD5 : Approx. 255g TDC-2104AFD5 : Approx. 190g